


Annex to Solar Keymark Certificate					Licence Number		011-7S3039 F							
					Date issued		2024-08-14							
					Issued by		DIN CERTCO							
Licence holder		Jiangsu Micoe Solar Energy Co., Ltd.			Country		China							
Brand (optional)		Micoe			Web		http://www.micoe.com							
Street, Number		No. 199, Yingzhou Road			E-mail		certification@micoe.com							
Postcode, City		222000, Lianyungang City, Jiangsu Province			Tel		+86 518-85959563							
Collector Type					Flat plate collector									
Collector name					Power output per collector									
					$G_b = 850 \text{ W/m}^2$, $G_d = 150 \text{ W/m}^2$ & $u = 1.3 \text{ m/s}$ $\vartheta_m - \vartheta_a$									
					0 K	10 K	30 K	50 K	70 K	77 K				
					W	W	W	W	W	W				
FPC1150D					1,50	1,000	1,500	80	1,093	1,039	921	788	640	588
FPC1200D					2.00	1,000	2,000	80	1,458	1,386	1,228	1,050	854	784
FPC1240D					2.40	1,200	2,000	80	1,749	1,663	1,473	1,260	1,025	941
FPC1270D					2.68	1,340	2,000	80	1,953	1,857	1,645	1,408	1,144	1,051
FPC1300D					3.00	1,500	2,000	80	2,186	2,079	1,841	1,576	1,281	1,176
Power output per m ² gross area					729	693	614	525	427	392				
Performance parameters test method		Steady state - outdoor												
Performance parameters (related to A _G)		η_0, b	a1	a2	a3	a4	a5	a6	a7	a8	Kd			
Units		-	W/(m ² K)	W/(m ² K ²)	J/(m ² K)	-	J/(m ² K)	s/m	W/(m ² K ⁴)	W/(m ² K ⁴)	-			
Test results		0.742	3.47	0.012	0.000	0.00	2612	0.000	0.00	0	0.88			
Incidence angle modifier test method		Steady state - outdoor												
Incidence angle modifier		Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°			
Transversal		$K_{GT, coll}$	1.00	1.00	0.99	0.97	0.92	0.84	0.70	0.45	0.00			
Longitudinal		$K_{GL, coll}$	1.00	1.00	0.99	0.97	0.92	0.84	0.70	0.45	0.00			
Heat transfer medium for testing					Water									
Flow rate for testing (per gross area, A _G)					dm/dt	0.020	kg/(sm ²)							
Maximum temperature difference during thermal performance test					$(\vartheta_m - \vartheta_a)_{max}$	46.67	K							
Standard stagnation temperature (G = 1000 W/m ² ; $\vartheta_a = 30 \text{ }^\circ\text{C}$)					ϑ_{stg}	170	°C							
Maximum operating temperature					$\vartheta_{max, op}$	120	°C							
Maximum operating pressure					$p_{max, op}$	1200	kPa							
Testing laboratory		Intertek Testing Services Shenzhen Ltd. Guangzhou Branch					http://www.intertek.com							
Test report(s)		230628124GZU-001					Dated		2024/8/14					
Comments of testing laboratory					Draft Ver. 6.2 (22.09.2021)									
All test results come from model FPC1150D					 Stamp & signature									
DIN CERTCO ● Alboinstraße 56 ● 12103 Berlin, Germany Tel: +49 30 7562-1131 ● Fax: +49 30 7562-1141 ● E-Mail: info@dincertco.de ● www.dincertco.de														

Annex to Solar Keymark Certificate		Licence Number													
Supplementary Information		011-7S3039 F													
		Issued													
		2024-08-14													
Gross Thermal Yield in kWh/collector at mean fluid temperature ϑ_m															
Standard Locations		Athens		Davos		Stockholm		Würzburg							
Collector name	ϑ_m	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C		
FPC1150D		1,723	1,222	794	1,308	901	565	961	626	378	1,044	674	401		
FPC1200D		2,298	1,630	1,059	1,744	1,201	754	1,281	834	504	1,392	899	534		
FPC1240D		2,757	1,956	1,271	2,093	1,442	904	1,538	1,001	604	1,670	1,079	641		
FPC1270D		3,079	2,184	1,419	2,337	1,610	1,010	1,717	1,118	675	1,865	1,205	716		
FPC1300D		3,446	2,444	1,588	2,616	1,802	1,131	1,922	1,252	755	2,088	1,349	801		
Gross Thermal Yield per m ² gross area		1,149	815	529	872	601	377	641	417	252	696	450	267		
Annual efficiency, η_a		65%	46%	30%	53%	37%	23%	55%	36%	22%	56%	36%	21%		
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)													
Annual irradiation on collector plane		1765 kWh/m ²			1630 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²				
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C				
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°				
The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Draft Ver. 6.2 (22.09.2021). A detailed description of the calculations is available at http://www.estif.org/solarkeymarknew/															
Additional Information															
Collector heat transfer medium										Water-Glycole					
The collector is deemed to be suitable for roof integration										No					
The collector was tested successfully under the following conditions:															
Climate class (A+, A, B or C)										B		--			
G (W/m ²) >		900		ϑ_a (°C) >		15		H_x (MJ/m ²) >		540					
Maximum tested positive load										5900		Pa			
Maximum tested negative load										3000		Pa			
Hail resistance using steel ball (maximum drop height)										2		m			
Additional collector attribute(s)															
Using external power source(s) for normal operation					No		Active or passive measure(s) for self-protection					No			
Co-generating thermal and electrical power					No		Façade collector(s)					No			
Energy Labelling Information							Additional Informative Technical Data								
		Reference Area, A_{sol} (m ²)			Hydraulic Designation Code				Aperture Area, A_a (m ²)						
FPC1150D		1.50			8-VH-1234S-A:9,1885-C22,1060-D				1.38						
FPC1200D		2.00			8-VH-1234S-A:9,1885-C22,1060-D				1.85						
FPC1240D		2.40			8-VH-1234S-A:9,1885-C22,1310-D				2.24						
FPC1270D		2.68			8-VH-1234S-A:9,1885-C22,1400-D				2.52						
FPC1300D		3.00			8-VH-1234S-A:9,1885-C22,1560-D				2.84						
Data required for CDR (EU) No 811/2013 - Reference Area A_{sol}							Data required for CDR (EU) No 812/2013 - Reference Area A_{sol}								
Collector efficiency (η_{col})		57%					Zero-loss efficiency (η_0)		0.73		--				
Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.		First-order coefficient (a_1)		3.47		W/(m ² K)									
		Second-order coefficient (a_2)		0.012		W/(m ² K ²)									
		Incidence angle modifier IAM (50°)		0.93		--									
							Remark: The data given in this section are related to collector reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.								
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany															
Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de															